HEAVY-DUTY
1/2" MAGNUM® DRILLS

0234-6
- WITH KEYED CHUCK

0235-21
- 1/2" MAGNUM® DRILL WITH ALL-METAL, GRIP-LOK™, SINGLE SLEEVE CHUCK
- INTERNAL SPINDLE LOCK–SINGLE HAND OPERATION TO TIGHTEN/LOOSEN CHUCK

0244-1
- WITH KEYED CHUCK

- **Powerful MILWAUKEE Built 5.5 AMP Motor**
- **Removable Brush Cartridge System** Change brushes in less than one minute, with only a screw-driver. Self-stopping brushes. Includes spare brushes stored in cartridge.

- **Aluminum Gear Case And Diaphragm Supplies Greater Support For Shaft And Bearings**
- **Heavy-Duty Industrial Chucks**
- **Trigger Speed Control Reversing Switches**
- **All Ball And Roller Bearings**
- **Helical Cut, Heat Treated Gears For Heavy-Duty Industrial/Construction Applications**
- **8' 3-Wire Quik-Lok® Cord Sets** Quick detachment from tool for tangle free carrying and storage. Instant field repair.

EXCLUSIVE 0235-21 FEATURE

- **All-Metal Grip-Lok™ Keyless Chucks** For extreme durability. Carbide jaws for long life. High gripping torque prevents slippage. Lightly knurled for comfortable grip.

SPECIFICATIONS

CATALOG NUMBER	CAPACITY IN STEEL	VOLTS AC ONLY	AMPS	NO LOAD RPM	GEAR TRAIN	SPINDLE DIAMETER AND THREAD	REPLACEMENT CHUCK CATALOG NO. CHUCK KEY INCLUDED	REPLACEMENT CHUCK KEY CATALOG NO.	LENGTH (IN.)	NET WGT. LBS.	SHIP. WGT. LBS.
0234-6	1/2"	120	5.5	0-850	DOUBLE	1/2" - 20	48-66-1360	48-66-3280	10-1/2	4.8	6.0
0235-21	1/2"	120	5.5	0-850	DOUBLE	1/2" - 20	48-66-1575	—	10-1/2	4.9	6.0
0244-1	1/2"	120	5.5	0-600	DOUBLE	1/2" - 20	48-66-1360	48-66-3280	10-1/2	4.8	6.0

STANDARD EQUIPMENT: FOR 0234-6 – 8' 3-Wire Quik-Lok Cord 48-76-4008, Chuck, Chuck Key, Rubber Flex Key Holder 48-66-4040 and Side Handle 49-15-0260. **FOR 0235-21 –** 8' 3-wire Quik-Lok Cord 48-76-4008, Single Sleeve Keyless Chuck and Side Handle 49-15-0260. **FOR 0244-1 –** 8' 3-Wire Quik-Lok Cord 48-76-4008, Chuck, Chuck Key, Rubber Flex Key Holder 48-66-4040 and Side Handle 49-15-0260.